



SPECIFICATIONS

Marketing Name	GeForce RTX™ 5060 8G VENTUS 2X OC V1
Model Name	G5060-8V2CV1
Graphics Processing Unit	NVIDIA® GeForce RTX™ 5060
Interface	PCI Express® Gen 5 x16 (uses x8)
Core Clocks	Extreme Performance: 2535 MHz (MSI Center) Boost: 2527 MHz
CUDA® CORES	3840 Units
Memory Speed	28 Gbps
Memory	8GB GDDR7
Memory Bus	128-bit
Output	DisplayPort x 3 (v2.1b) HDMI™ x 1 (As specified in HDMI™ 2.1b: up to 4K 480Hz or 8K 120Hz with DSC, Gaming VRR, HDR)
HDCP Support	Y
Power consumption	145 W
Power connectors	8-pin x1
Recommended PSU	550 W
Card Dimension (mm)	197 x 120 x 41 mm
Weight (Card / Package)	548 g / 840 g
DirectX Version Support	12 Ultimate
OpenGL Version Support	4.6
Maximum Displays	4
G-SYNC® technology	Y
Digital Maximum Resolution	7680 x 4320

CONNECTIONS



1. DisplayPort
2. HDMI™

FEATURES



Dual Fan

Two fans and a huge heatsink ensure a cool and quiet experience for you.




TORX FAN 5.0

Fan blades linked by ring arcs and a fan cowl work together to stabilize and maintain high-pressure airflow.



Reinforcing Backplate

The reinforcing backplate features a flow-through design that provides additional ventilation.



Zero Frozr

The fans completely stop when temperatures are relatively low, eliminating all noise.



Fuse

Additional fuses built into the custom PCB provide additional safeguards against electrical damage.



DrMOS

DrMOS power stage solutions provide great efficiency with low power loss and enhanced voltage controls.



MSI Center

The exclusive MSI Center software lets you monitor, tweak and optimize MSI products in real-time.



Afterburner

Take full control with the most recognized and widely used graphics card overclocking software in the world.