

Technical Specifications

Monitor	MF2408-A	What's in the box?
Diagonal Viewing Size	60.45 cm (23.8 inches)	Components
Horizontal	527.04mm	• Monitor with stand
Vertical	296.46 mm	• Adaptor
Maximum Preset Resolution	1920 x 1080 at 120 Hz	
Aspect Ratio	16:9	Cables
Pixel Pitch	0.2745×0.2745 mm	• 1 x HDMI cable
Pixel Per Inch (PPI)	92PPI	
Brightness	220±20 cd/m ² (typical)	
Color Support	Color depth: 16.7 Million	Documentation
Contrast Ratio	1500:1 (typical)	• User manual
Viewing Angle	178°/178°	
Response Time	5ms	
Panel Type	IPS	
Display Screen Coating	Matte	
Backlight Technology	LED	
Low Blue Light solution with	Yes (ComfortView)	
Flicker-free screen	Yes	
Connectivity		
Connectors	1 x VGA 1 x HDMI	
Design Features		
Adjustability	Tilt (-5° to 15°)	
Flat Panel Mount Interface	Not supported	
Environmental Parameters		
Min Operating Temperature	0°C	
Max Operating Temperature	40°C	
Humidity Range Operating	20%-80% (non-condensing)	
Power		
AC input voltage/frequency/current	100 VAC to 240 VAC / 50 Hz or 60 Hz ± 3 Hz / 1.5 A typical)	
	0.5 W (Off Mode)	
Power Consumption (Operational)	0.5 W (Standby Mode)	
	22.0W (On Mode)	
	36.0 W (Max)	
Power Consumption Stand by/Sleep	Less than 0.5W	
Dimensions (withstand)		
Height	407.7 mm	
Width	540.8mm	
Depth	190.6mm	
Weight		
Weight (with packaging)	3.7 KGS	
Carton size	594*104*386mm	