

Hellhound AMD Radeon™ RX 9070 GRE 12GB GDDR6

SPECIFICATION

EAN CODE	4713436176008	Bus Standard	PCIE 5.0 x16
Graphics Engine	RX9070GRE 12G-L/OC	Display Connectors	1 x HDMI 2.1b , 3 x DisplayPort 2.1a
Video Memory	12GB GDDR6	Form Factor	ATX
Stream Processor	3072 Units	Cooler	2 Slot Triple Fan
Engine Clock	Game 2280 MHz(OC)/ 2220 MHz(Silent)	Power Connector	Two 8-pin PCI Express Power Connector
	Boost 2860 MHz(OC)/ 2790 MHz(Silent)	OpenGL	4.6
Memory Speed	18.0 Gbps	DirectX® Support	12
Memory Interface	192-bit	Minimum System Power	700W
		Card Dimension(mm)	327*128*41mm 340*142*42mm(w/bracket)

Accessories Bundle Gaming Gear Intro Card


* 'Game Clock' is the expected GPU clock when running typical gaming applications, set to typical TGP (Total Graphics Power). Actual individual game clock results may vary.
* 'Boost Clock' is the maximum frequency achievable on the GPU running a bursty workload. Boost clock achievability, frequency, and sustainability will vary based on several factors, including but not limited to: thermal conditions and variation in applications and workloads.

FEATURES




Dual BIOS

Choosing the BIOS that fits your need: better overclocking or silent operation.



GPU Direct-Contact Copper Plate

A large copper plate provides direct contact with the GPU while covering VRAM area to increase the heat transfer threshold to the max.



Back Plate

The metal back plate is extremely rigid to strengthen the card to prevent PCB bending.



Intelligent Fan Controller

Utilizing temperature detection from a smart chip, fans will start running when the GPU reaches 60°C and shut down below 50°C.



Triple Ring-Fan

The 2X 100mm and 1X 90mm Ring-fan design improves the cooling performance.



Signature LED Color

Showcasing a cool and elegant aesthetic, the icy blue LED lighting sets a high-class tone.

The entire information provided herein are for reference only.
PowerColor reserves the right to modify or revise the content at anytime without prior notice.