Differentiator	4x HPE Smart Rate 1G/2.5GbE ports and 4x 1G/2.5G SFP uplink
Power consumption	16W, AC
Heat dissipation	28–65 BTU/hr depending on configuration
Input voltage	Rated voltage range: 100–240 VAC at 50 Hz or 60 Hz Maximum voltage range: 90–264 VAC at 47 Hz to 63 Hz
Ports	20x 10/100/1000BASE-T ports 4x 1G/2.5G BASE-T ports 4x 1G/2.5G BASE-X SFP ports 1x RJ-45 console port
Latency	1 GE: ≤5µs (64 byte LIFO)
Switching capacity	80 Gbps
Stacking capabilities	Two-switch IRF stack
Throughput	59.52 Mpps
Memory and processor	CPU: Single-core Arm® 1.25 GHz Flash: 256 MB Packet buffer: 0.5 MB
Power supply	Internal, 90V–264V AC
PoE capability	non-PoE
Operating temperature	-5°C–45°C (23°F–113°F)
Management features	Web GUI Command Line Interface (CLI) Smart Management Center (SmartMC) HPE Intelligence Management Center (IMC) HPE Networking Management Software (AirWave) SNMP RestAPI
Warranty	Limited lifetime hardware warranty. See the warranty duration.
Shipping weight	3 kg (6.614 lb)
Shipping dimensions	29.59 x 52.5 x 10.59 cm (11.65 x 20.67 x 4.17 in)
Fans	0