

DONANIM ÖZELLİKLERİ	
LED	Status
Boyutlar (W X D X H)	19.4 × 7.9 × 43.9 mm (0.76 × 0.3 × 1.73 in)
Anten	2× Dual-Band Antennas (Internal)

KABLOSUZ ÖZELLİKLERİ	
Kablosuz Standartlar	IEEE 802.11a/b/g/n/ac/ax
Bağlantı Hızı	5 GHz: 11ax: Up to 2402 Mbps(dynamic) 11ac: Up to 867 Mbps(dynamic) 11n: Up to 300 Mbps(dynamic) 11a: Up to 54 Mbps(dynamic) 2.4 GHz: 11ax: Up to 574 Mbps(dynamic) 11n: Up to 400 Mbps(dynamic) 11g: Up to 54 Mbps(dynamic) 11b: Up to 11 Mbps(dynamic)
Alıcı Hassasiyeti	5 GHz: 11ax HE160 MCS0: -86 dBm 11ax HE160 MCS11: -58 dBm 11ax HE20 MCS0: -91 dBm 11ax HE20 MCS11: -63 dBm 2.4 GHz: 11ax HE40 MCS0: -92 dBm 11ax HE40 MCS11: -63 dBm 11ax HE20 MCS0: -95 dBm 11ax HE20 MCS11: -65 dBm
Kablosuz Modları	Infrastructure mode
Kablosuz Güvenlik	WEP, WPA/WPA2/WPA3, WPA-PSK/WPA2-PSK
İletim Gücü	2.4 GHz: 13.5dbm(CE)(EIRP) 5 GHz: 10dbm(CE)(EIRP)

DİĞERLERİ	
Sertifika	FCC, CE, RoHS
Paket İçeriği	AX3000 Dual Band Wi-Fi 6 Wireless USB Adapter
Sistem Gereksinimleri	Supported operating systems include Windows 10, 11
Ortam	Operating Temperature: 0°C~40°C (32°F ~104°F) Operating Humidity: 10%~90% non-condensing Storage Humidity: 5%~90% non-condensing