LIQUID COOLING

MPG CORELIQUID P22 240 / W

RADIATE YOUR COOLING



FEATURES

2.1'' LCD

2.1-inch round IPS screen with curved glass for a stunning visual experience.

CYCLOBLADE 7

Focuses airflow and reduces noise.

Pre-installed Fans

Saves gamers installation time and enhances the assembly experience.

UNI Bracket

Easy installation: Pre-installed UNI Bracket (1700/1851/AM4/AM5)

EPDM Tubing

Durable and effective in preventing coolant evaporation.

SPECIFICATIONS

Pump	Speed: 3400±340 RPM Load Current: 0.21±0.042 A Power Consumption: 2.52±0.504 W Life Expectancy: 40℃,50000 hours
Water Block	Dimensions: 71.63 x 69.47 x 77.61 mm Panel Size: 2.1 Panel Type: IPS Panel Resolution: 540 x 540
Radiator	Size: 240 mm Dimensions: 277 x 119.2 x 27.2 mm Material: Aluminum
Tube	Length: 390 mm Material: EPDM+IIR
Fan	Size: 120 x 120 x 25 mm Quantity: 2 Speed: 500~2000±200 RPM RPM Air Flow: 62.6 CFM Air Pressure: 2.36 mm-H2O Noise: 31.1 dBA Bearing: Rifle Bearing Life Expectancy: 40℃,40000 Rated Current: 0.15±0.03 A (Set) Power Consumption: 1.8±0.36 W(Set) LED: ARGB GEN1
Compatibility	Intel: LGA 1700/ 1851 AMD: AM5、AM4

Generated 2026-11-09, check for the latest version www.msi.com/datasheet. The information provided in this document is intended for informational purposes only and is subject to change without notice.

© 2026 Micro-Star Int'l Co.Ltd. MSI is a registered trademark of Micro-Star Int'l Co.Ltd. All rights reserved.