HPE Networking Instant On Switch 48p Gigabit 4p SFP+ 1930

Differentiator Ports: 48 Gigabit copper
Uplink ports: 4 SFP+ 1/10 GbE ports

Power consumption 36.9W maximum, 16.8W idle

Input voltage 100 - 127 / 200 - 240 VAC

Ports 48 RJ-45 autosensing 10/100/1000 ports
(IEEE 802.3 Type 10 BASE-T, IEEE 802.3u
Type 100 BASE-TX, IEEE 802.3ab Type
1000 BASE-T);

Duplex: 10 BASE-T/100 BASE-TX: half or
full; 1000 BASE-T: full only
4 SFP+ 1/10 GbE ports

Switching capacity 176 Gbps

Throughput 130.95 Mpps, maximum

Memory and processor ARM Cortex-A9 @ 800 MHz
512 MB SDRAM, 256 MB flash
1.5 MB packet buffer

Operating temperature 32°F to 104°F (0°C to 40°C)

Management features Instant On Portal, Web browser, SNMP Manager

Warranty Limited lifetime warranty with 24X7 phone support for the first 90 days and chat support for the entire warranty duration.
Community support is available for the life of the product.

Weight 3.13 kg (6.91 lb)

Dimensions 4.39 x 44.25 x 28.24 cm (1.73 x 17.42 x 11.12 in)