HPE Networking Instant On Switch 8p Gigabit CL4 PoE 2p SFP 124W 1930

Differentiator Ports: 8 Gigabit copper
Uplink ports: 2 SFP 1 GbE ports.

Power consumption 150.2W maximum, 11.7W idle

Input voltage 100 - 127 / 200 - 240 VAC

Ports 8 RJ-45 autosensing 10/100/1000 Class 4 PoE ports
(IEEE 802.3 Type 10 BASE-T, IEEE 802.3u Type 100 BASETX, IEEE 802.3ab Type 1000 BASE-T)

Duplex: 10 BASE-T/100 BASETX: half or full; 1000 BASE-T: full only
2 SFP 1 GbE ports

Switching capacity 20 Gbps

Throughput 14.88 Mpps, maximum

Memory and processor ARM Cortex-A9 @ 800 MHz
512 MB SDRAM, 256 MB flash
1.5 MB packet buffer

PoE capability 124 W Class 4

Operating temperature 32°F to 104°F (0°C to 40°C)

Management features Instant On Portal, Web browser, SNMP Manager

Warranty Limited lifetime warranty with 24X7 phone support for the first 90 days and chat support for the entire warranty duration.
Community support is available for the life of the product.

Weight 1.16 kg (7.21 lb)

Dimensions 4.39 x 25.4 x 25.4 cm (1.73 x 10 x 10 in)