ZYXEL

Zyxel GS1900-48HPv2 Gözetilmiş L2 Gigabit Ethernet (10/100/1000) Ethernet üzerinden güç desteği (PoE) Siyah





Marka : Zyxel

Ürün kodu: GS190048HPV2-EU0101F

Ürün Adı : GS1900-48HPv2

Zyxel GS1900-48HPv2. Anahtar tipi: Gözetilmiş, Anahtar katmanı: L2. Temel açma kapama RJ-45 Ethernet giriş türü: Gigabit Ethernet (10/100/1000), Temel açma kapama RJ-45 Ethernet giriş sayısı: 48. Tam iki taraflı baskı. Adres tablosu boyutu: 8000 Kayıt, Yönlendirme/geçiş kapasitesi: 100 Gbit/s. Ağ standartı: IEEE 802.1Q, IEEE 802.1p, IEEE 802.3, IEEE 802.3ab, IEEE 802.3ad, IEEE 802.3af, IEEE 802.3at, IEEE.... Güç bağlantısı: DC giriş jakı. Ethernet üzerinden güç desteği (PoE). Raf montajı

Yönetim özellikleri	
Anahtar tipi *	Gözetilmiş
Anahtar katmanı	L2
Servis kalitesi (QoS) desteği	✔
MIB desteği	RFC 1213 MIB II, RFC 2819 RMON (group 1, 2, 3, 9), RFC 1215, RFC 1493
Bağlantı	
Temel açma kapama RJ-45 Ethernet giriş sayısı *	48
Temel açma kapama RJ-45 Ethernet giriş türü *	Gigabit Ethernet (10/100/1000)
SFP modülü yuva sayısı	2
Güç bağlantısı	DC giriş jakı
Ağ Bağlantıları	
Ağ standartı *	IEEE 802.1Q, IEEE 802.1p, IEEE 802.3, IEEE 802.3ab, IEEE 802.3ad, IEEE 802.3af, IEEE 802.3at, IEEE 802.3az, IEEE 802.3u, IEEE 802.3x
Bakır ethernet kablolama teknolojisi	1000BASE-T
Tam iki taraflı baskı	✔
VLAN desteği	✔
Veri aktarımı	
Yönlendirme/geçiş kapasitesi *	100 Gbit/s
Adres tablosu boyutu *	8000 Kayıt
Yedekle ve ilet	✔
Jumbo Frames desteği	✔
Tasarım	
Raf montajı *	✔
Ürün rengi	Siyah
İletişim LED göstergeleri	✔

Performans	
Gürültü seviyesi	36,9 dB
Enerji yönetimi	
AC girdi voltajı	100 - 240 V
AC girdi frekansı	50 - 60 Hz
Güç tüketimi (maksimum)	220,5 W
Eternet üzerindeki Güç (PoE)	
Ethernet üzerinden güç desteği (PoE) *	✔
Ethernet gücü (PoE) giriş sayısı	24
Ethernet bütçesi üzerindeki toplam güç	170 W
Çevresel koşullar	
Çalışma ısısı aralığı	0 - 50 °C
Depolama sıcaklığı aralığı (Celsius)	-40 - 70 °C
Çalıştırma nem aralığı	10 - 95%
Ağırlık & boyutlar	
Genişlik	441 mm
Derinlik	270 mm
Yükseklik	44 mm
Ağırlık	3,55 kg
Sertifikalar	
Sertifikalar, uygunluk bildirimleri	RoHS, CE
Lojistik veri	
Uyumlu Sistem (HS) kodu	85176990

4718937609543

5054444595955

Catalog Object Cloud

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.

Publication date: 19-OCT-2026. Prints or copies of Information are only valid on the printed Publication date