DONANIM ÖZELLİKLERİ	
Arabirim	• 9× 10/100/1000 Mbps RJ45 Ports (Ports 1–8 supports PoE+ output) • 1× Gigabit SFP Port
Ağ Medyası	• 10BASE-T: UTP category 3, 4, 5 cable (maximum 100m); EIA/TIA-568 100Ω STP (maximum 100m) • 100BASE-TX: UTP category 5, 5e cable (maximum 100m); EIA/TIA-568 100Ω STP (maximum 100m) • 1000BASE-T: UTP category 5, 5e, 6 or above cable (maximum 100m); EIA/TIA-568 100Ω STP (maximum 100m)
Fan Sayısı	Fanless
Kurulum	• Desktop • Wall Mounting
Fiziksel Güvenlik Kilidi	Yes
Güç Kaynağı	External Power Adapter(Output: 53.5VDC / 1.31A)
PoE Portları (RJ45)	• Standard: 802.3at/802.3af compliant • PoE Ports: Ports 1–8, up to 30 W PoE output per port • PoE Power Budget: 61W
Boyutlar (W X D X H)	8.2×4.9×1.0 in (209×126×26 mm)
Maks. Güç Tüketimi	• 7.3 W (220/50Hz. no PD connected) • 76.96 W (220/50Hz. with 61 W PD connected)
Max. Heat Dissipation	• 24.82 BTU/h (no PD connected) • 261.66 BTU/h (with 61 W PD connected)

PERFORMANS	
Anahtarlama Kapasitesi	20 Gbps
Paket Yönlendirme Hızı	14.88 Mpps
MAC Adres Tablosu	4K
Jumbo Frame	16 KB

YAZILIM ÖZELLİKLERİ	
Gelişmiş Özellikler	• Extend Mode Button (Ports 1–4, Up to 250 m PoE power supply and data transmission) • Isolation Mode Button (Ports 1–8) • PoE Auto Recovery Button (Ports 1–8) • Compatible With IEEE 802.3af/at Compliant PDs • IEEE802.3x Flow Control • 802.1p/DSCP QoS • IGMP Snooping • Green Technology
İletim Metodu	Store-And-Forward

DİĞERLERİ	
Sertifika	CE, FCC, RoHS
Paket İçeriği	• LS1210GP • Power Adapter • Installation Guide
Ortam	Operating Temperature: 0°C~40°C (32°F~104°F) Storage Temperature: -40°C~70°C (-40°F~158°F) Operating Humidity: 10% ~ 90% non-condensing Storage Humidity: 5%~90% non-condensing