

HPE Networking Instant On Switch 24p Gigabit CL4 PoE 4p SFP+ 195W 1930

Differentiator Ports: 24 Gigabit copper
Uplink ports: 4 SFP+ 1/10 GbE ports

Power consumption 280W maximum, 30W idle

Input voltage 100 - 127 / 200 - 240 VAC

Ports 24 RJ-45 autosensing 10/100/1000 Class 4 PoE ports
(IEEE 802.3 Type 10 BASE-T, IEEE 802.3u Type 100 BASE-TX, IEEE 802.3ab Type 1000 BASE-T)

Duplex: 10 BASE-T/100 BASE-TX: half or full; 1000 BASE-T: full only
4 SFP+ 1/10 GbE ports

Switching capacity 128 Gbps

Throughput 95.23 Mpps, maximum

Memory and processor ARM Cortex-A9 @ 800 MHz
512 MB SDRAM, 256 MB flash
1.5 MB packet buffer

PoE capability 195 W Class 4

Operating temperature 32°F to 104°F (0°C to 40°C)

Management features Instant On Portal, Web browser, SNMP Manager

Warranty Limited lifetime warranty with 24X7 phone support for the first 90 days and chat support for the entire warranty duration.
Community support is available for the life of the product.

Weight 3.49 kg (7.69 lb)

Dimensions 4.39 x 44.25 x 26.47 cm (1.73 x 17.42 x 10.42 in)