


Memory Module Specifications

KF552C36BBE-32TR

32GB 4G x 64-Bit

DDR5-5200 CL36 288-Pin DIMM



SPECIFICATIONS

CL(IDD)	40 cycles
Row Cycle Time (tRCmin)	48ns(min.)
Refresh to Active/Refresh Command Time (tRFCmin)	295ns(min.)
Row Active Time (tRASmin)	32ns(min.)
UL Rating	94 V - 0
Operating Temperature	0° C to +85° C
Storage Temperature	-55° C to +100° C

DESCRIPTION

Kingston KF552C36BBE-32TR is a 4G x 64-bit (32GB) DDR5-5200 CL36 SDRAM (Synchronous DRAM) 2Rx8, memory module, based on sixteen 2G x 8-bit FBGA components per module. The module supports AMD® EXPO v1.0 and Intel® Extreme Memory Profiles (Intel® XMP) 3.0. Each module has been tested to run at DDR5-5200 at a low latency timing of 36-40-40 at 1.25V. The SPDs are programmed to JEDEC standard latency DDR5-4800 timing of 40-39-39 at 1.1V. Each 288-pin DIMM uses gold contact fingers. The JEDEC standard electrical and mechanical specifications are as follows:

FEATURES

- Power Supply: VDD = 1.1V Typical
- VDDQ = 1.1V Typical
- VPP = 1.8V Typical
- VDDSPD = 1.8V to 2.0V
- On-Die ECC
- Height 1.37" (34.88mm), w/heatsink

FACTORY TIMING PARAMETERS

- Default (JEDEC): DDR5-4800 CL40-39-39 @1.1V
- EXPO Profile #0: DDR5-5200 CL36-40-40 @1.25V
- EXPO Profile #1: DDR5-4800 CL38-38-38 @1.1V
- XMP Profile #1: DDR5-5200 CL36-40-40 @1.25V
- XMP Profile #2: DDR5-4800 CL38-38-38 @1.1V

Continued >>

Technical drawing of the Kingston Beast DDR5 memory module. The top view shows a length of 133.35 mm and a width of 34.88 mm. The side view shows a height of 6.62 mm. The module features the Kingston Technology logo, the 'BEAST' branding, and 'DDR5' labeling. The drawing includes detailed outlines of the module's components, including the heat spreader and the memory chips.

(Tolerances on all dimensions are ± 0.15 unless otherwise specified)

Top View Dimensions (mm):

- Overall Width: 131.25
- Overall Height: 17.60
- Central Hole Diameter: $\varnothing 8.00$
- Central Hole Position (from left edge): 35.65
- Central Hole Position (from right edge): 45.85
- Central Hole Diameter: $\varnothing 8.00$
- Central Hole Position (from left edge): 35.65
- Central Hole Position (from right edge): 45.85
- Central Hole Diameter: $\varnothing 8.00$
- Central Hole Position (from left edge): 35.65
- Central Hole Position (from right edge): 45.85

Side View Dimensions (mm):

- Overall Width: 131.25
- Overall Height: 17.60
- Central Hole Diameter: $\varnothing 8.00$
- Central Hole Position (from left edge): 35.65
- Central Hole Position (from right edge): 45.85
- Central Hole Diameter: $\varnothing 8.00$
- Central Hole Position (from left edge): 35.65
- Central Hole Position (from right edge): 45.85
- Central Hole Diameter: $\varnothing 8.00$
- Central Hole Position (from left edge): 35.65
- Central Hole Position (from right edge): 45.85

Notes:

- R 0.65 MAX. 8 PLACES
- R 0.35x2
- RADIUS 1.50 2 PLACES
- RADIUS 0.80 2 PLACES

All Kingston products are tested to meet our published specifications. Some motherboards or system configurations may not operate at the published Kingston memory speeds and timing settings. Kingston does not recommend that any user attempt to run their computers faster than the published speed. Overclocking or modifying your system timing may result in damage to computer components.

Revision No.	History	Release Date	Remark	Editor	Approved
A	Initial Release	05/02/24		David Y.	Alex S.

*Products and specifications discussed herein are for evaluation and reference purposes only and are subject to change without notice. All information discussed herein is provided on an “as is” basis, without warranties of any kind.