ZYXEL

Zyxel XS1930-12F-ZZ0101F ağ anahtarı Gözetilmiş L2/L3 Siyah



Marka : Zyxel **Ürün kodu:** XS1930-12F-ZZ0101F

Ürün Adı : XS1930-12F-ZZ0101F

Zyxel XS1930-12F-ZZ0101F. Anahtar tipi: Gözetilmiş, Anahtar katmanı: L2/L3. Adres tablosu boyutu: 16000 Kayıt, Yönlendirme/geçiş kapasitesi: 240 Gbit/s. Ağ standartı: IEEE 802.1p, IEEE 802.1w, IEEE 802.1x, IEEE 802.3ab, IEEE 802.3ae, IEEE 802.3an, IEEE 802.3z. Güç bağlantısı: AC giriş jakı. Raf montajı

Yönetim özellikleri	
Anahtar tipi *	Gözetilmiş
Anahtar katmanı	L2/L3
Servis kalitesi (QoS) desteği	✔
Web-tabanlı yönetim	✔
ARP denetimi	✔
Konum Ayarlarının Konfigürasyonu (CLI)	✔
MIB desteği	✔

Bağlantı	
SFP+ modülü yuva sayısı	10
Güç bağlantısı	AC giriş jakı

Ağ Bağlantıları	
Ağ standartı *	IEEE 802.1p, IEEE 802.1w, IEEE 802.1x, IEEE 802.3ab, IEEE 802.3ae, IEEE 802.3an, IEEE 802.3z
10G desteği *	✔
Bağlantı geçidi aynalama	✔
Akış kontrol desteği	✔
Bağlantı kümeleme	✔
Yayım akımı kontrolü	✔
Ağaç protokolü süresi	✔
Ethernet LAN veri transfer hızı	1000,2500,5000,10000 Mbit/s
VLAN desteği	✔
VLAN adedi	4000

Veri aktarımı	
Yönlendirme/geçiş kapasitesi *	240 Gbit/s
İlerletme hızı	178,5 Mpps
Adres tablosu boyutu *	16000 Kayıt
Statik yol	✔
Jumbo Frames desteği	✔
Jumbo çerçeveler	12000
Paket ara belleği	2 MB

Güvenlik	
DHCP özellikleri	DHCP client, DHCP relay
Bağlantı kontrol listesi (ACL)	✔

Güvenlik	
IGMP aramak	✔
Güvenlik algoritması destekli	HTTPS, SHA-2, SSL/TLS
SSH/SSL desteği	✔
Döngü koruması	✔

Çoğa gönderim özellikleri	
Multicast desteği	✔

Tasarım	
Raf montajı *	✔
Ürün rengi	Siyah
İletişim LED göstergeleri	✔

Performans	
Dahili hafıza	256 MB
Flash bellek	32 MB

Enerji yönetimi	
Güç kaynağı *	AC
AC girdi voltajı	100 - 240 V
AC girdi frekansı	50 - 60 Hz
Güç tüketimi (maksimum)	24,9 W

Eternet üzerindeki Güç (PoE)	
Ethernet üzerinden güç desteği (PoE) *	✘

Çevresel koşullar	
Çalışma ısısı aralığı	-20 - 50 °C
Depolama sıcaklığı aralığı (Celsius)	-40 - 70 °C
Çalıştırma nem aralığı	5 - 95%
Çalışmama nemi	5 - 95%
Isı yayımı	84,91 BTU/s

Ağırlık & boyutlar	
Genişlik	484 mm
Derinlik	337 mm
Yükseklik	79 mm
Ağırlık	3,63 kg

Lojistik veri	
Uyumlu Sistem (HS) kodu	85176990

4718937620791

Catalog Object Cloud

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.

Publication date: 19-OCT-2026. Prints or copies of Information are only valid on the printed Publication date